



powertex® LE PF

Textile endless glass fiber,
voluminized and shape stable

PRODUCT CHARACTERISTICS

Low-emission formed part with inorganic binder which has outstanding acoustic properties as well as very good thermal resistance. Precise shape stability ensures easy handling and efficient installation.

TECHNICAL CHARACTERISTICS

Material	textile endless glass fiber	Transformation temperature (DIN ISO 7884-8)	761 °C
Fiber structure	glass (amorphous)	Softening temperature (DIN ISO 7884-5, analog ASTM C338)	925 °C
Specific density (glass)(ASTM D1505)	2,6 – 2,7 g/cm ³	Moisture content (PA 007-2, analog ISO 3344)	≤ 0,2 % *
Filament diameter (ISO 1888)	17 – 27 µm	Ignition loss (PA 007-2, analog ISO 1887)	≤ 0,65 % *
Linear density (ISO 1889)	3300 ± 600 tex	Resistance to acid (PA 013, 16 % HCl, 23 °C, 10 min)	≥ 99,0 % *
		Resistance to alkali (PA 015, 20 % NaOH, 50 °C, 24 h)	≥ 90,0 % *

BINDER CHARACTERISTICS

Binder type	inorganic	Combustibility	non combustible
Colour	white	Temperature resistance	> 1000 °C
Material	silicon based	Binder content	5 – 10 %
Morphology	amorphous		

* internal DBW test specification

The technical information does not constitute a quality warranty. The suitability purpose must be examined. Subject to change without notice.



DBW Advanced Fiber Technologies GmbH

Rodetal 40
37120 Bovenden
Deutschland

Technical contact person:

Matthias von Wensiersky
Tel. +49 (0)5594 801-11
matthias.wensiersky@dbw.de
www.dbw.de

Sales contact person:

Claudia Mahrt
Tel. +49 (0)5594 801-766
claudia.mahrt@dbw.de
www.dbw.de